Basic maintenance of the dental control unit

Tibor Fehértói mechanic

What does it need for operation?

- electricity
- compressed air
 treated water
- vacuum
- channel



Electricity

- lamp
- propulsion of handpieces
- control

You have to touch it, it won't SHOCK YOU.

Compressed air:

- turbine drive
- control

Treated water (softened, UV sterilized, constantly circulated):

- cooling of handpieces
- water in cup
 rinsing the cuspidor

Vacuum:

- saliva ejectorexhaustor


Channel:


- secration draining after separation

The filters

- Cuspidor
- Saliva ejector
- -inside filter

These are the most basic filters. Lack of cleaning can cause the chair's malfunction.










This is how it looks like many times:





Cooling of handpiece





Open to the left, close to the right. Max 1,5 turn !



Open to the left, close to the right. Max 1,5 turn!

Lubrication of handpiece



- Suitable adapter for the turbine, the straight and the elbowpiece.
- At least after every operation hours, but most importantly at the end of every day for about 1 second lubrication blowing is enough to extend the life of the handpiece.
- If it's done, we have to use the handpiece a little, so that the substance won't stuck into the handpiece until the next day (in the worst care from Friday to Monday.) because maybe for example the turbine won't work the next day. You have to be scared in that way either, put the drill bit into the turbine and twist it with your hand, then it will work.
- If there is possibility, keep the handpiece upside down.
- In case of the turbine not twisting when put on chair, don't be scared, the substance is able to hold the turbine that it won't start. In that case, twist a drill bit once and it will.

Cleaning


The sensitive wipes are capable of the cleaning of any part of the chair. We have to be aware to clean from the gaps and joints, so the dirt collected on the cleaning towel won't get in them.





λ

С



•Some more thoughts for the usage of the tools.



You have to exert serious force on the button. It is forbidden to twist in the meantime.

If you see even the smallest damage on the drill bit, it is forbidden to use because it can cause more damage on the handpiece and its repairing is much more expensive than the drill itself.



Thank you for listening!

Have a nice day!